

ANCO FOAMBREAK

Solutions Through Technology.....

Environmentally Friendly Chemicals

Product Description

ANCO FOAMBREAK is a readily dispersible, alcohol based blend of liquid surface active agents.

Typical Application

ANCO FOAMBREAK is an effective defoaming agent for all water based drilling fluids. ANCO FOAMBREAK is also an effective foam preventative for the preparation of saltwater / polymer fluid systems. ANCO FOAMBREAK is applicable wherever the presence of foam in the circulating system is problematic.

Product Advantages

- ANCO FOAMBREAK is effective at very low concentrations.
- Rapidly eliminates surface foam in the circulating system.
- Speeds the breakout of air and gas from aerated drilling fluids.
- Is an effective antifoaming agent for polymer mud systems.

Recommended Treatment

ANCO FOAMBREAK should be added (poured or sprayed) directly onto the surface of the drilling fluid system in the pits. ANCO FOAMBREAK provides effective defoaming action at concentrations as low as 0.006 gal/bbl (0.15 l/m³). The exact amount required should be determined (by pilot testing) prior to application.

Handling

Employees should use normal precautions when handling chemical products. The use of chemical gloves, apron, and safety goggles or face shield are recommended when adding this product. In case of eye contact, immediately flush with water for 15 minutes and seek medical advise. In case of skin contact, wash affected area with soap and water. Remove contaminated clothing and launder before reuse. Review Material Safety Data Sheet (MSDS) for this product prior to use.

Storage

ANCO FOAMBREAK should be stored in sealed containers at ambient temperatures, in an area protected from precipitation and excessive heat.

Packaging

Available in 5 gallon (25 liter) plastic pails.

Typical Chemical and Physical Properties

Specific Gravity g/cm ³	0.87
Flash Point, °F	149
Solubility	Completely miscible in water
Appearance	Transparent liquid
Color	Light Brown
Boiling Point, °F	392
pH	9.0