

ANCO GRAPHITE

Solutions Through Technology.....

Environmentally Friendly Chemicals

Product Description

ANCO GRAPHITE is a blend of natural amorphous graphite.

Typical Application

ANCO GRAPHITE may be used to increase slide rates when making angle corrections in horizontal drilling operations. It may also be used for any other application where use of a torque and drag reduces is indicated.

Product Advantages

- Reduces torque and drag.
- Effective at low concentrations.
- May be used in any type of water based fluids.
- Will not effect mud properties.

Recommended Treatment

For enhanced slide rates, ANCO GRAPHITE should be mixed in a pill using 3% - 5% by weight. This pill should then be circulated during slide operation. For use as a general mud lubricant, ANCO GRAPHITE should be added to the mud system through the mud hopper at 2% by weight.

Handling

No adverse health hazards are expected as a result of exposure to ANCO GRAPHITE; however, as with handling any chemical, good personal hygiene should be practiced. In case of contact with eye, flush with water for 15 minutes and obtain medical attention. Wash hands and other exposed areas with soap and water before eating.

Storage

Store in a dry area, protected from precipitation and contact by moisture.

Packaging

ANCO GRAPHITE is packaged in 50 lb multi-wall sacks.

Typical Chemical and Physical Properties

Specific Gravity g/cm ³	2.1
Appearance	Black Powder
Color	Black
Odor	None